

# DECKED

## LOAD LOCKS

### ALUMINUM RETAINER

Designed For Core Trax Tie-Down Systems

## - INSTRUCTIONS -

### TO INSERT LOAD LOCKS IN TRACK

Place second and third fingers under the wings of the Load Lock and place thumb on the top of the pin. Push down on the pin (like a syringe). Place Load Lock in any round opening on the track, then slide the Load Lock to the



narrow point (between two round openings) and release the wings.

**BE SURE THE LOAD LOCK SITS FLAT AGAINST THE TRACK BASE AND IS LOCKED IN PLACE, PARALLEL TO THE TRACK.**

### TO MOVE OR REMOVE THE LOAD LOCK

Place second and third fingers under the wings of the Load Lock and place thumb on the top of the pin. Pull upward with your fingers on the wings (like a syringe). Slide the Load Lock to the round opening on either side and lift the Load Lock off the track.

## IMPORTANT WARNING

Read and follow these instructions carefully. Inspect product before each use. **DO NOT USE** product if deformed, cracked, damaged or not securely installed. Avoid contact with objects, chemicals or flame that may damage or weaken the product. Product is not designed for use as a personal restraint or for towing. User is responsible for determining product's suitability for a particular purpose and shall assume all risks and liability in connection therewith. Improper use of the product may result in damage or severe injury. **Core Products USA** or **DECKED LLC** is not responsible for damage or injury caused by improper use of products.